



Republic of the Philippines
DEPARTMENT OF LABOR AND EMPLOYMENT
Occupational Safety and Health Center
North Avenue corner Agham Road, Diliman, Quezon City



OSHHC-QF-SCD-PPE-11

Revision No.: 02

Effective: February 20, 2019

SAFETY CONTROL DIVISION
PPE TESTING AND ASSESSMENT PROCEDURE

SAFETY SHOES TEST RESULTS

Request Reference Code: **PPE-SSHOES-2019-239**

BRAND NAME	KING'S	MODEL	KWD 301X-N	TYPE	BOOTS
DISTRIBUTOR	HONEYWELL SAFETY PRODUCTS				
ADDRESS	25th FLOOR, THE CURVE BUILDING, 32nd ST. BONIFACIO GLOBAL CITY, TAGUIG CITY				
Shoe Size: 9 <input checked="" type="checkbox"/> Men <input type="checkbox"/> Women Toe Cap Material: STEEL Toe Cap Specifications: 45.3 mm length 1.7 mm thickness 48.8 mm height 6.2 mm flange Mid-Sole Device Material: _____ Thickness _____ mm Manufacturing Process: <input type="checkbox"/> Direct Vulcanized <input type="checkbox"/> Cement <input type="checkbox"/> Goodyear Welt <input type="checkbox"/> Others, specify: _____ <input type="checkbox"/> Injection Mold				Remarks: Testing Standard: Occupational Safety and Health Standards Rule 1080: Personal Protective Equipment and Devices Based on PNS-ASTM F2412:2016 and PNS ASTM F2413:2016 Safety Shoes Test Classification: Class 75	
A. IMPACT RESISTANCE TEST					
Specimen Number	Impact Resistance Test Classification	Interior Height Clearance After Impact, mm	REMARKS	CRITERIA	
1	I-75	18.8	PASSED	The specimen shall have a minimum interior height clearance equal to or greater than the following: 12.7 mm for men's shoes and 11.9 mm for women's shoes	
2		19.2			
3		20.4			
B. COMPRESSION RESISTANCE TEST					
Specimen Number	Compression Resistance Test Classification	Interior Height Clearance After Compression, mm	REMARKS	CRITERIA	
1	C-75	21.0	PASSED	The specimen shall have a minimum interior height clearance equal to or greater than the following: 12.7 mm for men's shoes and 11.9 mm for women's shoes	
2		21.2			
3		20.8			
C. MIDSOLE DEVICE PUNCTURE RESISTANCE TEST					
Specimen Number	Minimum Puncture Resistance Requirement	Puncture Resistance kgf	REMARKS	CRITERIA	
1	122.5 kgf		TEST NOT CONDUCTED	The puncture resistant device shall pass if the tip of the test pin does not visually penetrate beyond the face of the material nearest the foot, after an applied force of 122.5 kgf.	
2					
3					



Republic of the Philippines
DEPARTMENT OF LABOR AND EMPLOYMENT
Occupational Safety and Health Center
North Avenue corner Agham Road, Diliman, Quezon City



OSHC-QF-SCD-PPE-11

Revision No.: 02

Effective: February 20, 2019

SAFETY CONTROL DIVISION
PPE TESTING AND ASSESSMENT PROCEDURE

SAFETY SHOES TEST RESULTS

Request Reference Code: **PPE-SSHOES-2019-239**

D. ELECTRICAL RESISTANCE TEST				
Specimen Number	Test Voltage V-AC	Leakage Current mA	REMARKS	CRITERIA
1	18,000 v		TEST NOT CONDUCTED	Electrically resistant protective footwear must be able to withstand an application of 18,000 volts for 1 minute with no leakage current in excess of 1 mA.
2				
3				
E. STATIC DISSIPATIVE TEST				
Specimen Number	Test Voltage V-DC	Electrical Resistance Megaohms	REMARKS	CRITERIA
1	50 v	2.86	PASSED	1 Megaohm to 100 Megaohms
2		2.68		
3		3.58		
COMMENTS: The specimens passed the requirements of PNS ASTM F 2413:2016 for Impact Resistance, Compression Resistance and Static Dissipative tests.				

Page 2 of 2

Test Conducted By:

MR. RONALD R. MATEO
Engineering Assistant

ENGR. DENNIS C. AQUINO
Engineer IV

Noted By:

ENGR. CONCEPCION T. STO. TOMAS
Chief, Safety Control Division

Date:

14 OCTOBER 2019

NOEL C. BINAG, CE
Executive Director